

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 372 301 A1

(12)

**EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC


(43) Date of publication:  
17.12.2003 Bulletin 2003/51(51) Int Cl.7: **H04L 12/56**, H04L 12/28,  
H04L 12/66(21) Application number: **02705324.8**(86) International application number:  
**PCT/JP02/02581**(22) Date of filing: **19.03.2002**(87) International publication number:  
**WO 02/076043 (26.09.2002 Gazette 2002/39)**(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**(30) Priority: **19.03.2001 JP 2001078740**  
**19.03.2001 JP 2001078741**  
**19.03.2001 JP 2001078742**(71) Applicant: **Sony Corporation**  
**Tokyo 141-0001 (JP)**(72) Inventors:  
• **KIMURA, Shinya**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**  
• **SASAKI, Takahiro**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**

- **NAKADE, Motoki**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**
- **KUNITO, Yoshiyuki**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**
- **HOKIMOTO, Akihiro**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**
- **OKA, Makoto**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**
- **MATSUYAMA, Shinako**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**
- **SHIONOZAKI, Atsushi**  
**Shinagawa-ku, Tokyo 141-0001 (JP)**

(74) Representative: **Horner, David Richard et al**  
**D Young & Co,**  
**21 New Fetter Lane**  
**London EC4A 1DA (GB)****(54) NETWORK SYSTEM**

(57) MTID of a terminal apparatus is preliminarily registered into a database of an ISP. In step S2, when a power source of the terminal apparatus is turned on first, (MTID = B) is transmitted from the terminal apparatus to a router. A transmission signal is received by the router and (HGWID = A, MTID = B) is transmitted

from the router to the ISP. If (HGWID = A, MTID = B) has been registered in the database, the ISP transmits a permission message in step S5. In step S6, an IP address for a new terminal apparatus is allocated and the new terminal apparatus can participate in a homenetwork. If (HGWID = A, MTID = B) is not registered, a refusal message is sent to the router.

**Fig. 4**

## Description

### Technical Field

[0001] The invention relates to a network system, a connecting apparatus, a connecting method, a network, a router, a terminal apparatus, a communicating method, a program, and a recording medium which can be applied to a case of connecting the network in a home to the Internet.

### Background Art

[0002] Contents transmitted into a home via the Internet is usually sent to a personal computer. Compression music data, image data, and the like which were downloaded are stored into the personal computer. The user tries to reproduce those contents which arrived at the personal computer by an AV (audio and/or visual) apparatus other than the personal computer. However, if a network in the home does not exist, it is difficult to realize such a request.

[0003] As network architectures, an Internet protocol system called TCP/IP (Transmission Control Protocol/Internet Protocol) used in the Internet and an OSI (Open System Interface) basic reference model have been known. The OSI reference model comprises seven layers. The first layer is a physical layer. The second layer is a data link layer. The third layer is a network layer. The fourth layer is a transport layer. The fifth layer is a session layer. The sixth layer is a presentation layer. The seventh layer is an application layer. In the physical layer, a physical mutual connection is made. Data is handled as a bit train here. In the data link layer, a physical communication path to a communication partner is assured and a competition control or the like is performed. Data is handled here as a unit such as a frame or the like which has been more structured.

[0004] The TCP/IP comprises four concept layers: a network interface layer, an Internet layer, a transport layer, and an application layer. Those layers are constructed on the physical layer. They can be made to correspond to those of the OSI reference model as follows: the data link layer → the network interface layer; the network layer → the Internet layer; the transport layer → the transport layer; the session layer, presentation layer, application layer → the application layer. The network interface layer is a layer for assuring communication in one subnetwork. For example, a PPP (Point-to-Point Protocol), for making communication between two points corresponds to the network interface layer.

[0005] The PPP (Point-to-Point Protocol) is a protocol which is used as a standard protocol by a dial-up IP connection. Data communication by a plurality of protocol authentication is provided by a line which is connected in a one-to-one correspondence relation. As a connecting procedure, a link is established via 1) a link establishing request, 2) authentication of a connecting per-

son, and 3) an information exchange of every protocol.

[0006] As networks in the home, wire transmission systems such as IEEE (Institute of Electrical and Electronics Engineers) 1394, Ethernet, and the like, and several wireless transmission systems have been proposed. As wireless transmission systems, IEEE802.11, Bluetooth (trademark), Wireless1394, and the like have been proposed. The networks in the home according to those various transmission systems construct an LAN (Local Area Network).

[0007] In recent years, the number of terminal apparatuses which are connected to the network in the home has been increasing. Each terminal apparatus is not limited to communication which is merely made to a specific target but is also connected to the Internet and can be also referred to from a network over the LAN. In order to allow the terminal apparatus to participate in such a network, there is needed a terminal apparatus called a router for at least allowing information to pass from one LAN to another LAN and enabling an information exchange with another terminal apparatus in the network to which the relevant terminal apparatus has been connected.

[0008] Although the setting of routing of the router is performed by the user, since the setting operation is technical and expert, when the user newly connects a terminal apparatus, it is necessary to execute the troublesome setting operation.

[0009] The foregoing general network architecture, for example, the TCP/IP protocol is also applied to the homenetwork. In the case where the homenetwork is a wireless network, in order to prevent the third person from looking surreptitiously, it is desirable to perform an authentication encryption at the level of the data link layer. Since the setting operation of the router having the wireless data link for such a purpose is technical and expert, when the user newly connects a terminal apparatus, it is necessary to execute the troublesome setting operation.

[0010] Further, from a point of protection of personal information, it is demanded that the homenetwork is a secure network. Hitherto, a firewall has been provided between the public network and the private network. This is because it is intended to prevent a person called a cracker who invade illegally the network. However, such a homenetwork depends on the provided firewall and the homenetwork does not become open, so that there is a problem such that it becomes an obstacle in case of developing a variety of kinds of applications.

[0011] It is, therefore, the first object of the invention is to provide a network system for enabling the user to easily connect a terminal apparatus to a router.

[0012] The second object of the invention is to provide a network system for enabling authentication at a data link level although the setting operation of a router having a wireless data link is unnecessary.

[0013] The third object of the invention is to provide a network system which can construct a secure network

without providing a firewall.

#### Disclosure of Invention

**[0014]** To solve the above problems, according to the invention of Claim 1, there is provided a network system comprising: a router for permitting or refusing a connection on the basis of one identifier which a terminal apparatus has; and a database in which the router and the terminal apparatus connected thereto have previously been associated,

wherein when there is a connecting request from the terminal apparatus, the database is referred to on the basis of the request and in the case where a correspondence of the router and the terminal apparatus has been recorded in the database, the connection of the terminal apparatus which is connected is permitted.

**[0015]** According to the invention of Claim 2, there is provided a connecting apparatus in which a network including a router and one or more terminal apparatuses is provided on a terminal side and which provides a service for connecting to the Internet to the terminal side, comprising:

a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to the network has been registered,

wherein when a terminal apparatus is newly connected to the network, whether a correspondence relation between an identifier of the router which is sent from the user's side and an identifier of the terminal apparatus exists in the database or not is discriminated, and

at least one of permission information which is formed when the correspondence relation exists and used to permit the connection of the new terminal apparatus to the network and refusal information which is formed when the correspondence relation does not exist and used to refuse the connection of the new terminal apparatus to the network is transmitted to the terminal side.

**[0016]** According to the invention of Claim 5, there is provided a connecting method in which a network including a router and one or more terminal apparatuses is provided on a terminal side and which provides a service for connecting to the Internet to the terminal side, wherein

a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to the network has been registered,

when a terminal apparatus is newly connected to the network, whether a correspondence relation between the identifier of the router which is sent from the user's side and an identifier of the terminal apparatus exists in the database or not is discriminated, and

at least one of permission information which is

formed when the correspondence relation exists and used to permit the connection of the new terminal apparatus to the network and refusal information which is formed when the correspondence relation does not exist and used to refuse the connection of the new terminal apparatus to the network is transmitted to the terminal side.

**[0017]** According to the invention of Claim 8, there is provided a network which is constructed by a router having one identifier and one or more terminal apparatuses each having one identifier and connected to an Internet connecting apparatus via the router, wherein

when a terminal apparatus is newly connected to the network, a correspondence relation between the identifier of the router and an identifier of the terminal apparatus is transmitted to the Internet connecting apparatus, at least one of permission information and refusal information formed by the Internet connecting apparatus on the basis of a result of a discrimination with reference to a database is received, and

the terminal apparatus can be newly connected only in the case where a fact that the correspondence relation exists in the database is shown by at least one of the permission information and the refusal information.

**[0018]** According to the invention of Claim 11, there is provided a program for a network which is constructed by a router having one identifier and one or more terminal apparatuses each having one identifier and connected to an Internet connecting apparatus via the router, wherein

the program allows the network to execute:

a procedure for, when a terminal apparatus is newly connected to the network, transmitting a correspondence relation between the identifier of the router and an identifier of the terminal apparatus to the Internet connecting apparatus;

a procedure for receiving at least one of permission information and refusal information formed by the Internet connecting apparatus on the basis of a result of a discrimination with reference to a database; and

a procedure for newly connecting the terminal apparatus only in the case where a fact that the correspondence relation exists in the database is shown by at least one of the permission information and the refusal information.

**[0019]** According to the invention of Claim 12, there is provided a recording medium on which a program for a network which is constructed by a router having one identifier and one or more terminal apparatuses each having one identifier and connected to an Internet connecting apparatus via the router has been recorded, wherein

the program allows the network to execute:

a procedure for, when a terminal apparatus is newly connected to the network, transmitting a correspondence relation between the identifier of the router and an identifier of the terminal apparatus to the Internet connecting apparatus;

a procedure for receiving at least one of permission information and refusal information formed by the Internet connecting apparatus on the basis of a result of a discrimination with reference to a database; and

a procedure for newly connecting the terminal apparatus only in the case where a fact that the correspondence relation exists in the database is shown by at least one of the permission information and the refusal information.

**[0020]** According to the invention, only in case of a combination of the router and the terminal apparatus which has been registered in the database provided for an Internet service provider, the connection is permitted to the network such as a homenetwork or the like. The user does not need to set the router by himself and can easily allow the terminal apparatus to participate newly in the network such as a homenetwork or the like. It is also possible to prevent an unregistered terminal apparatus from being connected to the network such as a homenetwork or the like, so that the security of the network can be improved.

**[0021]** To solve the above problems, according to the invention of Claim 13, there is provided a network system in which a router and a terminal apparatus are connected in a wireless manner, wherein

one identifier is recorded, a removable recording medium is provided,

the recording medium is loaded into the router and, thereafter, attached to the terminal apparatus, and

the router reads out the identifier, thereby allowing a link between the router and the terminal apparatus specified by the identifier to be established.

**[0022]** According to the invention of Claim 16, there is provided a router for exchanging information between terminal apparatuses connected in a wireless manner, wherein

one identifier is recorded, a removable recording medium is provided, the identifier is read out from the loaded recording medium, and

a link with the terminal apparatus which is specified by the identifier is established.

**[0023]** According to the invention of Claim 19, there is provided a terminal apparatus for exchanging information in a wireless manner, wherein

one identifier is recorded, a removable recording medium is detachably provided, the identifier is read out from the loaded recording medium, and

a link is established by the identifier at the time of wireless communication.

**[0024]** According to the invention of Claim 20, there is provided a communicating method in a network sys-

tem in which a router and a terminal apparatus are connected in a wireless manner, comprising:

a step wherein one identifier is recorded and a removable recording medium is provided;

a step wherein the recording medium is loaded into the router and the router reads out the identifier;

a step wherein the recording medium is attached to the terminal apparatus and the terminal apparatus reads out the identifier; and

a step wherein the router detects that the terminal apparatus is specified by the identifier, thereby establishing a link between the router and the terminal apparatus.

**[0025]** According to the invention of Claim 21, there is provided a program for a network system in which a router, a terminal apparatus are connected in a wireless manner and one identifier is recorded, and a removable recording medium is provided, wherein

the program allows the network system to execute:

a step wherein the recording medium is loaded into the router and the router reads out the identifier;

a step wherein the recording medium is attached to the terminal apparatus and the terminal apparatus reads out the identifier; and

a step wherein the router detects that the terminal apparatus is specified by the identifier, thereby establishing a link between the router and the terminal apparatus.

**[0026]** According to the invention of Claim 22, there is provided a recording medium on which a program for a network system in which a router and a terminal apparatus are connected in a wireless manner, one identifier is recorded, and a removable recording medium is provided has been recorded, wherein

the program allows the network system to execute:

a step wherein the recording medium is loaded into the router and the router reads out the identifier;

a step wherein the recording medium is loaded into the terminal apparatus and the terminal apparatus reads out the identifier; and

a step wherein the router detects that the terminal apparatus is specified by the identifier, thereby establishing a link between the router and the terminal apparatus.

**[0027]** According to the invention, the recording medium is loaded into the router and the router reads out the identifier on the recording medium, so that the authentication for allowing the router and the terminal apparatus which is specified by the identifier to communicate can be performed. Therefore, the user does not

need to execute the troublesome operation such as setting of the router or the like.

[0028] Further, to solve the foregoing problems, according to the invention of Claim 23, there is provided a network system in which a server and a router are connected via a network and one or more terminal apparatuses are connected to the router, wherein

the server has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses connected to the network has been registered,

when the first and second terminal apparatuses communicate with each other, the server is inquired about whether the identifiers of the first and second terminal apparatuses have been registered as a same group onto the database or not, and

when the correspondence relation exists, the first and second terminal apparatuses can communicate.

[0029] According to the invention of Claim 26, there is provided a terminal apparatus which is connected to a network system, wherein

when there is a communicating request from another terminal apparatus, an external server is inquired about an identifier of such another terminal apparatus via a router,

whether such another terminal apparatus belongs to a same group or not is discriminated with reference to a database of the server, and

only when such another terminal apparatus belongs to the same group, communication with such another terminal apparatus can be made.

[0030] According to the invention of Claim 28, there is provided a communicating method in a network system in which a server and a router are connected via a network, one or more terminal apparatuses are connected to the router, and the server has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to the network has been registered, comprising the steps of:

when the first and second terminal apparatuses communicate with each other, inquiring of the server about whether the identifiers of the first and second terminal apparatuses have been registered as a same group onto the database or not; and when the correspondence relation exists, determining that the first and second terminal apparatuses can communicate.

[0031] According to the invention of Claim 31, there is provided a program for a communicating method in a network system in which a server and a router are connected via a network, one or more terminal apparatuses are connected to the router, and the server has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to the network has been

registered, wherein

the program allows the network system to execute the steps of:

when the first and second terminal apparatuses communicate with each other, inquiring of the server about whether the identifiers of the first and second terminal apparatuses have been registered as a same group onto the database or not; and when the correspondence relation exists, determining that the first and second terminal apparatuses can communicate.

[0032] According to the invention of Claim 32, there is provided a recording medium on which a program for a communicating method in a network system in which a server and a router are connected via a network, one or more terminal apparatuses are connected to the router, and the server has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to the network has been registered has been recorded, wherein

the program allows the network system to execute the steps of:

when the first and second terminal apparatuses communicate with each other, inquiring of the server about whether the identifiers of the first and second terminal apparatuses have been registered as a same group onto the database or not; and when the correspondence relation exists, determining that the first and second terminal apparatuses can communicate.

[0033] According to the invention, by referring to an identifier of a partner side with which communication is made, whether the partner's identifier belongs to the same group as a user's own identifier or not is discriminated for the database provided for the server. If it belongs to the same group, it is determined that the authentication between the terminals is satisfied, so that the link is established. The secure network can be constructed without implementing a firewall, and the homenetwork can be set to be open.

#### Brief Description of Drawings

[0034]

Fig. 1 is a block diagram showing a construction of a network system according to the first embodiment of the invention.

Fig. 2 is a block diagram showing an example of a construction of a router in the first embodiment of the invention.

Fig. 3 is a flowchart for explaining processes in case of allowing a new terminal apparatus to participate

in a homenetwork in the first embodiment of the invention.

Fig. 4 is a block diagram showing a construction of a network system according to the second embodiment of the invention.

Fig. 5 is a block diagram showing a construction of the network system in the second embodiment of the invention.

Fig. 6 is a block diagram showing an example of a construction of a router in the second embodiment of the invention.

Fig. 7 is a flowchart for explaining an authenticating process at a data link level in the second embodiment of the invention.

Fig. 8 is a block diagram showing a construction of the network system in the second embodiment of the invention.

Fig. 9 is a flowchart for explaining a terminal authenticating process in the second embodiment of the invention.

Fig. 10 is a block diagram showing a construction of the network system in the second embodiment of the invention.

Fig. 11 is a block diagram showing a construction of the network system in the second embodiment of the invention.

#### Best Mode for Carrying Out the Invention

(First embodiment)

[0035] An embodiment of the invention will be described hereinbelow. Fig. 1 shows an example of a system of the first embodiment of the invention. Reference numeral 1 denotes an Internet; 2 indicates an ISP (Internet Service Provider) connected to the Internet 1. The ISP 2 has a mail server, a DNS (Domain Name System) server, a Proxy server, and the like, provides an ordinary Internet connecting function, and has a database 3 for authentication.

[0036] Reference numeral 11 denotes a home; and 12 indicates a home gateway, for example, a router. The ISP 2 and router 12 are connected by a bidirectional access line 4 such as ISDN (Integrated Services Digital Network) line, dedicated line, xDSL (x Digital Subscriber Line) like an ADSL (Asymmetric Digital Subscriber Line) or the like, optical fiber, or the like. In case of using the ISDN line as a bidirectional access line 4, a DSU (Digital Service Unit) (not shown) and a TA (Terminal Adapter) if necessary are inserted between the router 12 and the ISDN line.

[0037] A service company of a cable television can be also connected by using a cable television line as a bidirectional access line 4. The service company distributes audio and/or visual contents via a cable television base station and a digital set-top box provided in the home 11. Such a service company of the cable television is also a kind of ISP 2 for providing a service for

connecting to the Internet.

[0038] In the embodiment, a homenetwork such as an wireless LAN shown at reference numeral 13 is installed in the home 11. IEEE802.11x including IEEE802.11, Bluetooth, Wireless1394, or the like can be used as a wireless LAN. The homenetwork 13 is not limited to the wireless LAN but a wire LAN using a telephone line, a power line, or a cable can be also used. Further, the homenetwork 13 can also include a plurality of networks. For example, it is also possible to connect a cellular phone by the wireless LAN and connect the cellular phone to another apparatus by Bluetooth.

[0039] A terminal apparatus 14 is connected to the homenetwork 13. Reference numeral 15 denotes a terminal apparatus to be newly connected to the homenetwork 13. A personal computer (desktop type or notebook-sized type), an audio apparatus such as a CD (Compact Disc) player or the like, a television concerning apparatus such as tuner, display, or the like, a video recorder/player such as a DVD (Digital Versatile Disc or Digital Video Disc) apparatus or the like, or a terminal apparatus such as a portable information apparatus or the like can be connected to the homenetwork 13. Further, household appliances such as air-conditioner, refrigerator, and the like can be connected to the homenetwork 13.

[0040] Various data is supplied from the ISP 2 via the router 12 to each of the terminal apparatuses connected to the homenetwork 13. For example, contents data such as audio data, video data, etc. is supplied to the router 12. At the same time, the terminal apparatuses connected to the homenetwork 13 can communicate with each other.

[0041] Fig. 2 schematically shows a construction of the router 12. The router 12 comprises: a media access control unit 21; a route control unit 22; a wireless control unit 23; an inquiry unit 24; and an access line media access control unit 26. The media access control unit 21 controls transmission of data to a transmission medium such as a wireless LAN (homenetwork 13). A plurality of terminal apparatuses 14 and 15 are mutually connected by the wireless control unit 23 in a wireless manner. The route control unit 22 is connected to the bidirectional access line 4. The inquiry unit 24 communicates with the ISP 2 via the media access control unit 21 and route control unit 23 and inquires of the ISP 2 about permission or refusal of connection of the new terminal apparatus 15.

[0042] Each of the router 12 and the terminal apparatuses 14 and 15 has one ID (identifier) in the ISP. The ID of the terminal apparatus is expressed by MTID and the ID of the router 12 is expressed by HGWID.

[0043] Information of a combination of HGWID of the router 12 and MTID of the terminal apparatus has previously been registered in the database 3 provided for the ISP 2. For example, a registering process to the database 3 is executed by a sales shop which sold the terminal apparatus. Specifically speaking, assuming that

HGWID of the router 12 is set to HGWID = A and MTID of the terminal apparatus 15 is set to MTID = B, when the user purchases the terminal apparatus 15, the user brings by himself a card in which HGWID of the router 12 at home has been recorded to the shop. On the basis of information of the router and information of the terminal apparatus 15, the shop registers data showing a correspondence relation of (HGWID = A and MTID = B) into the database 3. A symbol added to the ID has a meaning for specifying each ID and does not denote a value of the data. A data construction of the ID has a predetermined format such as a bit length or the like and, preferably, has been encrypted.

[0044] The registering method into the database 3 is not limited to the above method. For example, if a contract for sale has been made via the Internet 1 and ISP 2, on the basis of the information of the router to which the terminal apparatus in which software for such communication has been implemented is connected, the ISP 2 or the receiving side of an order can register the data indicative of the correspondence relation between HGWID of the router and MTID of the terminal apparatus into the database 3.

[0045] A flow of processes which are executed at the time when the new terminal apparatus 15 is connected to the homenetwork 13 will be described with reference to Fig. 3. The flow of those processes corresponds to a program which is installed into the router 12 or another computer and which controls the homenetwork 13. As necessary, this program is recorded into a computer-readable recording medium. Step S1 relates to a process for preliminarily registering MTID of the terminal apparatus (TE) 15 into the database 3 as mentioned above and it is executed separately from subsequent processes.

[0046] In step S2, if the initial operation of the terminal apparatus 15, for example, the operation to first turn on a power source is executed in the home 11, the user transmits (MTID = B) from the terminal apparatus 15 to the router 12. A transmission signal of the terminal apparatus 15 is received by the wireless control unit 23 of the router 12. MTID is supplied to the inquiry unit 24 via the media access control unit 21.

[0047] The inquiry unit 24 can process a signal including MTID from the terminal apparatus 15 which is not registered yet into the homenetwork 13. In the inquiry unit 24, HGWID of the router 12 has been held. (HGWID = A and MTID = B) is transmitted from the inquiry unit 24 to the ISP 2 via the route control unit 22, access line media access control unit 26, and bidirectional access line 4 (step S3).

[0048] The ISP 2 discriminates whether the combination of the IDs (HGWID = A and MTID = B) has been registered in the database 3 or not by referring to the database 3. If it has been registered, that is, if matching is satisfied in step S4, the ISP 2 transmits a permission message to the router 12 via the bidirectional access line 4 in step S5.

[0049] In the router 12, the permission message is sent to the inquiry unit 24 via the access line media access control unit 26, route control unit 22, and media access control unit 21 of the router 12. In step S6, in case of an IPv4 (Internet Protocol version 4), an IP address is allocated to the new terminal apparatus 15 by a DHCP (Dynamic Host Configuration Protocol, RFC 2131). In case of IPv6, an IP network prefix is allocated. Thus, the new terminal apparatus 15 can participate in the homenetwork 13. Various settings which are necessary for connecting the terminal apparatus 15 to the homenetwork 13 are also executed by the permission message and the user himself hardly needs to perform the setting operation.

[0050] If it is determined in step S4 that the combination of the IDs (HGWID = A and MTID = B) is not registered in the database 3 yet, a refusal message is sent to the inquiry unit 24 via the route control unit 22 and media access control unit 21 of the router 12 in step S7. In this case, since the router 12 recognizes that the new terminal apparatus is an apparatus which must not be connected to the homenetwork 13, this terminal apparatus cannot participate in the homenetwork 13.

(Second embodiment)

[0051] Fig. 4 shows an example of a system according to the second embodiment of the invention. Reference numeral 101 denotes an Internet and 102 indicates an ISP (Internet Service Provider) serving as a server connected to the Internet 101. The ISP 102 has a mail server, a DNS (Domain Name System) server, a Proxy server, and the like, provides an ordinary Internet connecting function, and has a database 103 for authentication.

[0052] Reference numeral 111 denotes a home; and 112 indicates a home gateway, for example, a router. The ISP 102 and router 112 are connected by a bidirectional access line 104 such as ISDN (Integrated Services Digital Network) line, dedicated line, xDSL (x Digital Subscriber Line) like an ADSL (Asymmetric Digital Subscriber Line) or the like, optical fiber, or the like. In case of using the ISDN as a bidirectional access line 104, a DSU (Digital Service Unit) (not shown) and a TA (Terminal Adapter) if necessary are inserted between the router 112 and the ISDN.

[0053] A service company of a cable television can be also connected by using a cable television line as a bidirectional access line 104. The service company distributes audio and/or visual contents via a cable television base station and a digital set-top box provided in the home 111. Such a service company of the cable television is also a kind of ISP 102 for providing a service for connecting to the Internet.

[0054] In the embodiment, a wire LAN shown at reference numeral 113 and a wireless LAN 114 are installed in the home 111. The wire LAN 113 and wireless LAN 114 construct a homenetwork. IEEE802.11x includ-

ing IEEE802.11, Bluetooth, Wireless1394, or the like can be used as a wireless LAN 114. The homenetwork can also include another network. For example, it is also possible to connect a cellular phone by the wireless LAN and connect the cellular phone to another apparatus by Bluetooth. Although the invention is characterized by a connection control of an apparatus which is connected in a wireless manner, the embodiment will be described with respect to an apparatus which exists mixedly with an apparatus which is connected by a wire.

[0055] Terminal apparatuses TE1, TE2, and TE3 are connected to the wire LAN 113. TE4 denotes a terminal apparatus to be newly connected to the wireless LAN 114. A personal computer (desktop type or notebook-sized type), an audio apparatus such as a CD (Compact Disc) player or the like, a television concerning apparatus such as tuner, display, or the like, a video recorder/player such as a DVD (Digital Versatile Disc or Digital Video Disc) apparatus or the like, or a portable information apparatus, or the like can be connected as a terminal apparatus. Further, household appliances such as air conditioner, refrigerator, and the like can be connected to the homenetwork.

[0056] Various data is supplied from the ISP 102 via the router 112 to each of the terminal apparatuses connected to the wire LAN 113 and wireless LAN 114. For example, contents data such as audio data, video data, etc. is supplied to the router 112. At the same time, the terminal apparatuses connected to the wire LAN 113 and/or the wireless LAN 114 can communicate with each other.

[0057] In case of the homenetwork which is managed by the ISP 102, each terminal apparatus has one identifier in the ISP. The ISP 102 preliminarily records the identifier onto a recording medium (that is, removable recording medium) which is detachable to/from the terminal apparatus. As a recording medium, it is possible to use an information recording medium which can generally hold information, such as IC card (also called a memory card) for recording information into a flash memory, magnetic card for recording information onto a magnetic material, plastic card for recording information as a graphic pattern such as a bar code or the like, or the like. In the embodiment, the IC card is used. The IC card can also have a function of an LAN card or the like in addition to a function for holding the identifier. The router 112 also has an identifier (ID:0) of the router itself.

[0058] The IC card in which the identifier (ID) has been recorded is detachable to/from the router 112 and each terminal apparatus. (ID:1) is recorded in an IC card MS1 loaded into the terminal apparatus TE1. (ID:2) is recorded in an IC card MS2 loaded into the terminal apparatus TE2. (ID:3) is recorded in an IC card MS3 loaded into the terminal apparatus TE3. Further, ID:4) is recorded in an IC card MS4 which is loaded into the terminal apparatus TE4. A numeral added to the ID has a meaning for specifying each ID and does not denote a value of the data. A data construction of the ID has a

predetermined format such as a bit length or the like and, preferably, has been encrypted.

[0059] If the user intends to connect the terminal apparatus TE4 to the wireless LAN 114, he requests the ISP 102 to issue a new identifier (ID:4). That is, the user receives distribution of the IC card MS4 on which such an identifier has been recorded. Fig. 4 shows a stage at which the user obtained the IC card MS4. As shown in Fig. 5, the IC card MS4 is loaded into the router 112. The router 112 reads out the identifier (ID:4) from the IC card MS4 and stores it into the router 112. In other words, (ID:4) is previously registered into the router 112.

[0060] After completion of the reading of the identifier and storing into the router 112, the IC card MS4 is removed from the router 112 and loaded again into the terminal apparatus TE4. When the terminal apparatus TE4 communicates with the router 112, by transmitting the identifier (ID:4), authentication at the data link level between the router 112 and the terminal apparatus TE4 is performed. It is also possible to generate an encryption key by using the identifier (ID:4) and encrypt contents of communication as necessary.

[0061] As mentioned above, by inserting the IC card MS4 into the router 112 and, subsequently, inserting the IC card MS4 into the terminal apparatus TE4, the authentication at the data link level can be performed. Thus, it is possible to prevent an unauthorized person from looking surreptitiously the contents of the communication of the wireless LAN 114. That is, it is possible to prevent the third person from connecting to the wireless LAN 1 from the outside of the house where the router 112 has been installed. Further, in the embodiment, for the purpose of performing the terminal authentication, the correspondence relation between the ID of the router and the ID of the terminal apparatus has been registered onto the database 3 which the ISP 102 has. The ID of the router 112 is expressed by HGWID.

[0062] Information of a combination of HGWID of the router 112 and the ID of the terminal apparatus has previously been registered in the database 103 provided for the ISP 102. For example, a registering process to the database 103 is executed by the ISP 102 and a sales shop when the terminal apparatus is sold. For example, when the user purchases the terminal apparatus TE4, the user brings by himself a card in which HGWID of the router 112 at home has been recorded to the shop. On the basis of information of the router and information of the IC card MS4, the shop registers data showing a correspondence relation of (HGWID : 0, ID : 4) into the database 103. Together with the terminal apparatus TE4, the user obtains the IC card MS4 on which (ID : 4) has previously been recorded.

[0063] Naturally, the registering method into the database 103 is not limited to the above method. For example, if a sales contract has been made via the Internet 101 and ISP 102, on the basis of the information of the router to which the terminal apparatus in which software for such communication has been implemented is con-



nected, the ISP 102 or the receiving side of an order can register the data indicative of the correspondence relation between HGWID of the router and the ID of the terminal apparatus into the database 103.

[0064] Fig. 6 schematically shows a construction of the router 112. The router 112 comprises: a wireless media access control unit 121; a route control unit 122; a wireless control unit 123; an inquiry unit 124; an IC card interface 125; an access line media access control unit 126; and a wire media access control unit 127. The wireless media access control unit 121 controls transmission of data to the wireless LAN 114. The wire media access control unit 127 controls transmission of data to the wire LAN 113.

[0065] A plurality of terminal apparatuses are mutually connected in a wireless manner by the wireless control unit 123. The route control unit 122 is connected to the bidirectional access line 104. The inquiry unit 124 communicates with the ISP 102 via the wireless media access control unit 121, route control unit 122, and access line media access control unit 126 and inquires of the ISP 102 about permission or refusal of connection of a new terminal apparatus. The IC card interface 125 is an interface of the IC card and can read out the identifier recorded in a predetermined format. Further, key data or the like can be recorded onto the IC card as necessary.

[0066] The authenticating process at the data link level will be described with reference to a flowchart of Fig. 7. A flow of this process corresponds to a program which is installed into the router 112 or another computer and which controls the wireless LAN 114. As necessary, this program is recorded onto a computer-readable recording medium. However, step S10 relates to a process for previously registering the ID into the database 103 as mentioned above and it is executed separately from subsequent processes.

[0067] In first step S11, the IC card is inserted into the router 112. The identifier, for example, (ID:4) recorded in the IC card is read out via the IC card interface 125 of the router 112. Subsequently, in step S12, the IC card is returned (loaded) into the terminal apparatus TE4. Upon communication, in step S13, the terminal apparatus TE4 notifies the router 112 of (ID:4). The router 112 recognizes that the terminal apparatus TE4 has the same ID as the read-out ID. In this manner, the authentication at the data link level between the router 112 and the terminal apparatus TE4 is satisfied in step S14.

[0068] Subsequently, the terminal authentication is performed. The terminal authentication is necessary irrespective of the wire manner or the wireless manner and a secure network can be constructed without installing the firewall and performing packet filtering or the like. The terminal authentication will be described hereinbelow.

[0069] Fig. 8 shows a state where the IC cards MS1, MS2, and MS3 have been loaded into the terminal apparatuses TE1, TE2, and TE3 connected to the wire

LAN 113, respectively, and the identifiers recorded in those IC cards have been registered in the database 103 of the ISP 102. As a method of registering the identifiers of the terminal apparatuses connected to the wire LAN 113 into the database 103, a method similar to that mentioned above can be used.

[0070] A flow for the terminal authenticating process will be described with reference to Fig. 9. A flow of this process corresponds to a program which is installed into the router 112 or another computer and which controls the wire LAN 113 and wireless LAN 114. As necessary, this program is recorded onto a computer-readable recording medium. The registering process of the ID into the database has previously been executed.

[0071] For example, a case where the terminal apparatus TE4 (ID:4) communicates with the terminal apparatus TE3 (ID:3) will be described as an example. In step S21, the terminal apparatus TE4 requests the terminal apparatus TE3 to establish the link. In step S22, the terminal apparatus TE3 which received this request inquires of the ISP 102 via the router 112 about whether the terminal apparatus TE4 belongs to the same group or not. The inquiry unit 124 of the router 112 also transmits the identifier (ID:0) of the router 112 to the ISP 102 in an interlocking relational manner. Desirably, the communication for authentication has been encrypted.

[0072] In step S23, the ISP 102 refers to the database 103. In step S24, whether (ID:3) and (ID:4) belong to the same group or not is discriminated. (1, 2, 3, 4) have been registered as IDs in the database 103 with respect to (HGWID:0) (refer to Figs. 4 and 5). Therefore, it is determined that (ID:3) and (ID:4) belong to the same group.

[0073] This result is transmitted from the ISP 102 to the router 112 via the bidirectional access line 104, access line media access control unit 126, and route control unit 122 and, further, transmitted from the router 112 to the terminal apparatus TE3. In case of the same group, the terminal authentication is satisfied (step S25). In step S26, the security between the terminal apparatuses TE3 and TE4 is established. If it is determined in step S24 that they do not belong to the same group, the terminal authentication is not satisfied (step S27). In this case, the security is not established (step S28). In order to assure the security of the homenetwork, if the IC card is pulled out from the terminal apparatus after the link was established, the establishment of the security is invalidated.

[0074] Fig. 10 shows a situation where the terminal apparatus registered in a homenetwork of the third person has been connected to the user's own homenetwork. Another terminal apparatus is assumed to be TE10, its IC card is assumed to be MS10, and its identifier is assumed to be (ID:10). In this case, the IC card MS10 is loaded into the router 112, thereby allowing the router 112 to read out (ID:10). Thus, the authentication at the data link level is satisfied. However, in the database 103 of the ISP 102, (ID:10) is not registered as an

ID of the same group as that of the router 112 (HGW ID: 0). Therefore, terminal authentication is not satisfied.

[0075] This means that although the terminal apparatus TE10 can be connected to the Internet 101 via the router 122 and to the homenetwork of that person, it cannot communicate with the terminal apparatus connected to the wire LAN 113 and wireless LAN 114. That is, there is an advantage such that the terminal apparatus having a mechanism for authentication at the data link level using the IC card can communicate with the outside via another homenetwork having a similar mechanism.

[0076] Further, Fig. 11 shows an example in which a terminal apparatus, for example, TE4 is brought to the outside of the home and communication is made via a public access point 131. The IC card MS4 on which (ID: 4) has been recorded has been loaded into the terminal apparatus TE4. In this case, however, since the IC card MS4 cannot be loaded to the router 112 existing at a remote position, the authentication at the data link level is omitted. However, the public access point 131 can have a construction such that previous registration of the identifier by the IC card can be accepted.

[0077] The terminal apparatus TE4 can access the Internet 101 via the public access point 131 and, further, can communicate with the terminal apparatus of the homenetwork of his own home. In this case, the terminal authentication as mentioned above is executed. Only when the terminal authentication is satisfied, the security is established. As mentioned above, even in the terminal apparatus which is used by the homenetwork, it can be carried out to the outside of the home and used.

[0078] The invention is not limited to the foregoing embodiment of the invention but many modifications and applications are possible within the scope without departing from the spirit of the invention. For example, although the foregoing embodiment has been described with respect to the example of the homenetwork, the invention is not limited to the home but can be also applied to a network in a company.

#### Industrial Applicability

[0079] According to the invention, the network system in which only a combination of the router and the terminal apparatus which has been registered in the database provided for the Internet service provider can be connected to the network can be realized. The user does not need to set the router by himself but can enable the terminal apparatus to participate newly in the network such as a homenetwork or the like. According to the invention, it is possible to prevent the unregistered terminal apparatus from being connected to the network such as a homenetwork or the like, so that the security of the network can be improved. For example, a cellular phone which can be connected to the network can be limited to a cellular phone having a function for preventing an illegal invasion from the outside.

[0080] According to the invention, even in the case

where the homenetwork is a wireless network, in order to prevent the third person from looking surreptitiously, the authentication at the data link level can be performed. The security can be improved by the terminal authentication. Further, there is an advantage such that the setting operation of the router or the like for such a purpose becomes unnecessary and it is sufficient to execute the loading and removing operations of the recording medium.

[0081] Further, according to the invention, the secure network can be constructed without implementing the firewall. There is, consequently, an advantage such that a problem in which the homenetwork depends on the implemented firewall and the homenetwork does not become an open network does not occur.

#### Claims

##### 1. A network system comprising:

a router for permitting or refusing a connection on the basis of one identifier which a terminal apparatus has; and  
a database in which the router and the terminal apparatus connected thereto have previously been associated,

wherein when there is a connecting request from said terminal apparatus, said database is referred to on the basis of said request and in the case where a correspondence of said router and said terminal apparatus has been recorded in said database, the connection of said terminal apparatus which is connected is permitted.

##### 2. A connecting apparatus in which a network including a router and one or more terminal apparatuses is provided on a terminal side and which provides a service for connecting to the Internet to the terminal side, comprising:

a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to the network has been registered,

wherein when a terminal apparatus is newly connected to said network, whether a correspondence relation between an identifier of the router which is sent from the user's side and an identifier of the terminal apparatus exists in said database or not is discriminated, and

at least one of permission information which is formed when said correspondence relation exists and used to permit the connection of said new terminal apparatus to said network and refusal information which is formed when said correspondence

- relation does not exist and used to refuse the connection of said new terminal apparatus to said network is transmitted to said terminal side.
3. A connecting apparatus according to claim 2, wherein
    - when the terminal apparatus is sold, the correspondence relation between the identifier of the router and the identifier of the terminal apparatus which is connected to the network is registered into said database.
  4. A connecting apparatus according to claim 2, wherein
    - when an order is made via the Internet, the correspondence relation between the identifier of the router and the identifier of the terminal apparatus which is connected to the network is registered into said database by a person who receives said order.
  5. A connecting method in a network system including a router and one or more terminal apparatuses on a terminal side, wherein said network system has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to a network has been registered, and in said network system, a service for connecting to the Internet is provided to the terminal side,
    - whereby when a terminal apparatus is newly connected to said network system, whether a correspondence relation between the identifier of the router which is sent from the user's side and an identifier of said terminal apparatus exists in said database or not is discriminated, and
    - at least one of permission information which is formed when said correspondence relation exists and used to permit the connection of said new terminal apparatus to said network system and refusal information which is formed when said correspondence relation does not exist and used to refuse the connection of said new terminal apparatus to said network system is transmitted to said terminal side.
  6. A connecting method according to claim 5, wherein
    - when the terminal apparatus is sold, the correspondence relation between the identifier of the router and the identifier of the terminal apparatus which is connected to the network is registered into said database.
  7. A connecting method according to claim 5, wherein
    - when an order is made via the Internet, the correspondence relation between the identifier of the router and the identifier of the terminal apparatus which is connected to the network is registered into said database by a person who receives said
  - order.
  8. A network system which is constructed by a router having one identifier and one or more terminal apparatuses each having one identifier and connected to an Internet connecting apparatus via said router, wherein
    - when a terminal apparatus is newly connected to said network system, a correspondence relation between the identifier of the router and an identifier of said terminal apparatus is transmitted to said Internet connecting apparatus, at least one of permission information and refusal information formed by said Internet connecting apparatus on the basis of a result of a discrimination with reference to a database is received, and
    - the terminal apparatus can be newly connected only in the case where a fact that said correspondence relation exists in said database is shown by at least one of said permission information and said refusal information.
  9. A network system according to claim 8, wherein
    - when the terminal apparatus is sold, the correspondence relation between the identifier of the router and the identifier of the terminal apparatus which is connected to a network is registered into said database.
  10. A network system according to claim 8, wherein
    - when an order is made via the Internet, the correspondence relation between the identifier of the router and the identifier of the terminal apparatus which is connected to a network is registered into said database by a person who receives said order.
  11. A program for a network system which is constructed by a router having one identifier and one or more terminal apparatuses each having one identifier and connected to an Internet connecting apparatus via said router, wherein
    - said program allows said network system to execute:
      - a procedure for, when a terminal apparatus is newly connected to said network system, transmitting a correspondence relation between the identifier of the router and an identifier of said terminal apparatus to said Internet connecting apparatus;
      - a procedure for receiving at least one of permission information and refusal information formed by said Internet connecting apparatus on the basis of a result of a discrimination with reference to a database; and
      - a procedure for newly connecting the terminal apparatus only in the case where a fact that

said correspondence relation exists in said database is shown by at least one of said permission information and said refusal information.

12. A recording medium on which a program for a network system which is constructed by a router having one identifier and one or more terminal apparatuses each having one identifier and connected to an Internet connecting apparatus via said router has been recorded, wherein

said program allows said network system to execute:

a procedure for, when a terminal apparatus is newly connected to said network system, transmitting a correspondence relation between the identifier of the router and an identifier of the terminal apparatus to said Internet connecting apparatus;

a procedure for receiving at least one of permission information and refusal information formed by said Internet connecting apparatus on the basis of a result of a discrimination with reference to a database; and

a procedure for newly connecting the terminal apparatus only in the case where a fact that said correspondence relation exists in said database is shown by at least one of said permission information and said refusal information.

13. A network system in which a router and a terminal apparatus are connected in a wireless manner, wherein

one identifier is recorded, a removable recording medium is provided,

said recording medium is loaded into said router and, thereafter, attached to the terminal apparatus, and

said router reads out said identifier, thereby allowing a link between the router and the terminal apparatus specified by said identifier to be established.

14. A network system according to claim 13, wherein the identifier has previously been written onto said recording medium on a connecting apparatus side.

15. A network system according to claim 13, wherein a point that said recording medium has been attached to said terminal apparatus is used as a condition for establishment of the link.

16. A router for exchanging information between terminal apparatuses connected in a wireless manner, wherein

one identifier is recorded, a removable recording medium is detachably provided,

said identifier is read out from said loaded recording medium, and

a link with the terminal apparatus which is specified by said identifier is established.

17. A router according to claim 16, wherein the identifier has previously been written onto said recording medium on a connecting apparatus side.

18. A router according to claim 16, wherein a point that said recording medium has been attached to said terminal apparatus is used as a condition for establishment of the link.

19. A terminal apparatus for exchanging information in a wireless manner, wherein

one identifier is recorded, a removable recording medium is detachably provided,

said identifier is read out from said loaded recording medium, and

a link is established by said identifier at the time of wireless communication.

20. A communicating method in a network system in which a router and a terminal apparatus are connected in a wireless manner, comprising:

a step wherein one identifier is recorded and a removable recording medium is provided;

a step wherein said recording medium is loaded into said router and said router reads out said identifier;

a step wherein said recording medium is attached to said terminal apparatus and said terminal apparatus reads out said identifier; and

a step wherein said router detects that said terminal apparatus is specified by said identifier, thereby establishing a link between said router and said terminal apparatus.

21. A program for a network system in which a router and a terminal apparatus are connected in a wireless manner, one identifier is recorded, and a removable recording medium is provided, wherein said program allows said network system to execute:

a step wherein said recording medium is loaded into said router and said router reads out said identifier;

a step wherein said recording medium is attached to said terminal apparatus and said terminal apparatus reads out said identifier; and

a step wherein said router detects that said terminal apparatus is specified by said identifier, thereby establishing a link between said router and said terminal apparatus.

22. A recording medium on which a program for a network system in which a router and a terminal apparatus are connected in a wireless manner, one identifier is recorded, and a removable recording medium is provided has been recorded, wherein

said program allows said network system to execute:

a step wherein said recording medium is loaded into said router and said router reads out said identifier;

a step wherein said recording medium is attached to said terminal apparatus and said terminal apparatus reads out said identifier; and  
a step wherein said router detects that said terminal apparatus is specified by said identifier, thereby establishing a link between said router and said terminal apparatus.

23. A network system in which a server and a router are connected via a network and one or more terminal apparatuses are connected to said router, wherein said server has a database in which a correspondence relation between an identifier of said router and identifiers of said terminal apparatuses connected to the network has been registered,

when the first and second terminal apparatuses communicate with each other, said server is inquired about whether the identifiers of said first and second terminal apparatuses have been registered as a same group onto said database or not, and

when said correspondence relation exists, said first and second terminal apparatuses can communicate.

24. A network system according to claim 23, wherein one or more identifiers are registered into said database every identifier of the router.

25. A network system according to claim 23, wherein the identifier of said terminal apparatus has been recorded on a recording medium which is removable to/from said terminal apparatus.

26. A terminal apparatus which is connected to a network system, wherein

when there is a communicating request from another terminal apparatus, an external server is inquired about an identifier of said another terminal apparatus via a router,

whether said another terminal apparatus belongs to a same group or not is discriminated with reference to a database of said server, and

only when said another terminal apparatus belongs to the same group, communication with said another terminal apparatus can be made.

27. A terminal apparatus according to claim 26, wherein

whether said another terminal apparatus belongs to the same group or not is determined by checking whether a correspondence relation between an identifier of said router and an identifier of said terminal apparatus exists on said database or not.

28. A communicating method in a network system in which a server and a router are connected via a network, one or more terminal apparatuses are connected to said router, and said server has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to said network has been registered, comprising the steps of:

when the first and second terminal apparatuses communicate with each other, inquiring of said server about whether the identifiers of said first and second terminal apparatuses have been registered as a same group onto said database or not; and  
when said correspondence relation exists, determining that said first and second terminal apparatuses can communicate.

29. A communicating method according to claim 28, wherein

one or more identifiers are registered into said database every identifier of the router.

30. A communicating method according to claim 28, wherein

the identifier of said terminal apparatus has been recorded on a recording medium which is removable to/from said terminal apparatus.

31. A program for a communicating method in a network system in which a server and a router are connected via a network, one or more terminal apparatuses are connected to said router, and said server has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to said network has been registered, wherein

said program allows said network system to execute the steps of:

when the first and second terminal apparatuses communicate with each other, inquiring of said server about whether the identifiers of said first and second terminal apparatuses have been registered as a same group onto said database or not; and  
when said correspondence relation exists, determining that said first and second terminal apparatuses can communicate.

32. A recording medium on which a program for a communicating method in a network system in which a server and a router are connected via a network, one or more terminal apparatuses are connected to said router, and said server has a database in which a correspondence relation between an identifier of the router and identifiers of the terminal apparatuses which are connected to said network has been registered has been recorded, wherein  
said program allows said network system to execute the steps of:

when the first and second terminal apparatuses communicate with each other, inquiring of said server about whether the identifiers of said first and second terminal apparatuses have been registered as a same group onto said database or not; and  
when said correspondence relation exists, determining that said first and second terminal apparatuses can communicate.

25

30

35


40

45


50

55

**Fig. 1**



**Fig. 2**





**Fig. 3**




Fig. 4






Fig. 5



**Fig. 6**



***Fig. 7***





Fig. 8



**Fig. 9**




Fig. 10







Fig. 11



DESCRIPTION OF REFERENCE NUMERALS

- 1, 101    INTERNET
- 2, 102    ISP
- 3, 103    DATABASE
- 12, 112   ROUTER
- 13       HOME NETWORK
- 14, 15, TE1~TE4, TE10       TERMINAL APPARATUS
- 113      WIRE LAN
- 114      WIRELESS LAN
- MS1~MS4, MS10       IC CARD
- S1       REGISTER MTID OF TE
- S2       TE TRANSMITS MTID = B TO ROUTER
- S3       ROUTER TRANSMITS HGWID = A AND MTID = B TO ISP
- S4       MATCHING IS OK?
- S5       ISP TRANSMITS PERMISSION MESSAGE TO ROUTER
- S6       ALLOCATE IP ADDRESS TO TE
- S7       ISP TRANSMITS REFUSAL MESSAGE TO ROUTER
- S8       DISPLAY ERROR
- S10      (ID = 4) IS REGISTERED INTO BASE DATA AND RECORDED INTO IC CARD BY  
          ISP
- S11      IC CARD IS INSERTED INTO ROUTER
- S12      RETURN IC CARD TO TERMINAL
- S13      TERMINAL NOTIFIES ROUTER OF ID = 4
- S14      AUTHENTICATION OF DATA LINK LEVEL IS OK

EP 1 372 301 A1

S21 COMMUNICATING REQUEST FROM TERMINAL (ID = 4) TO TERMINAL (ID = 3)  
S22 TERMINAL (ID = 3) INQUIRES OF ISP  
S23 ISP REFERS TO DATABASE  
S24 (ID = 3) AND (ID = 4) BELONG TO SAME GROUP?  
S25 TERMINAL AUTHENTICATION IS OK  
S26 SECURITY IS ESTABLISHED  
S27 TERMINAL AUTHENTICATION IS NG  
S28 SECURITY IS NOT ESTABLISHED

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP02/02581

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> Int.Cl <sup>7</sup> H04L12/56, H04L12/28, H04L12/66  According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) Int.Cl <sup>7</sup> H04L12/56, H04L12/28, H04L12/66, H04L9/32  Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1926-1996 Toroku Jitsuyo Shinan Koho 1994-2002 Kokai Jitsuyo Shinan Koho 1971-2002 Jitsuyo Shinan Toroku Koho 1996-2002  Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X P, Y	JP 2001-144812 A (Sharp Corp.), 25 May, 2001 (25.05.01), Full text; all drawings (Family: none)	1-12 23-32
Y	JP 2000-236342 A (Nippon Telegraph And Telephone Corp.), 29 August, 2000 (29.08.00), Par. Nos. [0004] to [0006]; Figs. 1, 8 (Family: none)	13-22
Y	JP 10-285658 A (Canon Inc.), 23 October, 1998 (23.10.98), Abstract; Claims 1, 2; Par. No. [0025] (Family: none)	13-22
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 24 April, 2002 (24.04.02)		Date of mailing of the international search report 14 May, 2002 (14.05.02)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1998)

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP02/02581

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, Y	JP 2001-189722 A (Toshiba Corp.), 10 July, 2001 (10.07.01), Abstract; Par. Nos. [0033] to [0061] (Family: none)	13-22
Y	JP 2001-53901 A (Sony Corp.), 23 February, 2001 (23.02.01), Claims 1 to 3; Fig. 1 (Family: none)	23-32
A	JP 11-331181 A (Toppan Printing Co., Ltd.), 30 November, 1999 (30.11.99), Par. Nos. [0006] to [0010] (Family: none)	1-32
P, A	JP 2001-306519 A (NTT Communications Kabushiki Kaisha), 02 November, 2001 (02.11.01), Par. Nos. [0030] to [0045] (Family: none)	1-32

Form PCT/ISA/210 (continuation of second sheet) (July 1998)

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP02/02581

**Box I** Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
  
2. ☐ Claims Nos.:  
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
  
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

**Box II** Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

Claims 1-12 are directed to an idea of permitting a connection to a terminal which has made a connection request if the correspondence relationship between the terminal and a router which has received the connection request is registered in a connection permission table.

Claims 13-22 are directed to an idea of assigning the same identifier to a router which receives a connection request and a terminal which makes the connection request and allowing the router to permit the connection of the terminal which has the same identifier as that of the router.

1. ☒ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
  
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
  
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
  
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest ☐ The additional search fees were accompanied by the applicant's protest.  
☒ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP02/02581

Continuation of Box No. II of continuation of first sheet (1)

Claims 23-32 are directed to an idea of determining permission/rejection of communication between terminals depending on whether or not the terminals belong to the same group.

These three groups of inventions are not so linked as to form a single general inventive concept.